



Odorless, Virgin Mineral Spirits/
Waterless Cleaner

A waterless tacking liquid cleaner

Typical Coverage for Tacking:

- 900–1000 square feet per gallon

Note: Do NOT use this product with automatic scrubbers or wet vacuums. Do not use this product or store in an area when temperature is above 95°F.

Be aware some dark-soled shoes may be softened by Buckeye Coliseum Odorless, Virgin Mineral Spirits / Waterless Cleaner and leave marks on the floor. White-soled shoes are preferred.

Features:

- Easy-to-use
- Odorless
- Waterless cleaner
- Not reclaimed mineral spirits
- Mild fragrance
- Dries with minimal residue

Available in:



Other Equipment needed:

- Low-speed, single disc floor machine (175 rpm) with 20-inch, #120 grit screens (depending on floor inspection)
- 24-inch or 36-inch push broom (for sweeping and tacking)
- Terry cloth towels for tacking
- Putty knife or scraper
- Heavyweight T-bar (18" or 24")

Surface Preparation:

Follow MFMA and NOFMA guidelines for wood acclimation time prior to installation, sanding, and coating.

Make certain that the floor is clear of contamination including oils, silicones, waxes, fillers, and stains that contain stearates as they may cause adhesion problems.

DIRECTIONS

This product is designed to be used as is (DO NOT DILUTE). Thinning or reducing with solvents is not recommended.

1. Remove tape, gum, and debris from the floor using a putty knife.
2. Dust mop floor to remove any loose dirt.

DRY SCREENING:

1. Floor must be dry before screening with a #100, #120 or #150 grit screen.
2. After screening, vacuum well, then tack the floor with **Buckeye Coliseum Odorless, Virgin Mineral Spirits / Waterless Cleaner** to remove any remaining dust.
3. Continue tacking until the towel is free of dust.
4. Allow the floor to dry. Once dry, the floor is ready for Coliseum solvent-based, oil-modified urethane coating.

WET SCREENING:

Low dust generated.

1. Mop a 100 ft² area with **Buckeye Coliseum Odorless, Virgin Mineral Spirits / Waterless Cleaner**.
2. With an **EXPLOSION PROOF FLOOR MACHINE**, screen the area with a #100, #120 or #150 grit screen.
3. Repeat steps 1 and 2 until the entire floor is completed.
4. Tack the floor with **Buckeye Coliseum Odorless, Virgin Mineral Spirits / Waterless Cleaner** until the towel is free of dust.
5. Allow the floor to dry.
6. Check the floor for unscreened patches. If there are no unscreened patches, the floor is ready for Coliseum solvent-based, oil-modified urethane coating.

Note: Allow **Buckeye Coliseum Odorless, Virgin Mineral Spirits / Waterless Cleaner** to evaporate completely before coating application. Look along any cracks, board spaces, nail holes, and other areas along the walls for wet, damp or dark areas. These regions may not accept coating and may delay the coating dry time.

WARNING! Combustible Liquid and Vapor. May cause eye and respiratory tract irritation. Prolonged or repeated contact may dry the skin and cause cracking and irritation. Harmful if swallowed. May cause lung damage.

Troubleshooting

Slow dry – low curing temperatures, high humidity, air movement, or lack of ventilation after application.

Streaks – result when coating is applied too thin.

Fisheyes – foreign material on the surface such as oil, grease, or silicone.

Wrinkling – recoating too soon; results when application is too heavy, puddling the coating.

Bubbling – results when coating is overworked with the applicator including shaking the coating before application or high temperatures during application.

Peeling – improper floor prep.

Dirt particles – result when the applicator is not “de-fuzzed” causing loose fibers in the film or when the room vents are not sealed off during application.

Screen marks – result when an overly-aggressive screen is used between coats.

Technical Specifications:

Weight/Gallon	6.16–6.46 lbs.
Color	Water clear
Flash Point	>110°F
Distillation Range	340°F–410°F
Aromatics	<0.25%v/v

Buckeye International, Inc.

2700 Wagner Place • Maryland Heights • MO 63043
800.321.2583 • www.buckeyereflections.com