



Bulletin Number: 1510

Buckeye Wood Floor Painting Instructions

*Proper prep procedures (located on Coliseum 100, Coliseum 200, Coliseum Low VOC Sanding Seal, Larry's Super 40 and Arena 50 Catalog Sheets) are to be followed if painting over Buckeye Reflections sealers.

*If painting during a screen and recoat, be sure to abrade painted areas with a dry 3M SPP Pad and tack with Screen Clean Ready to Use Floor Prep Cleaner and Tacking Solution to ensure adhesion before attempting further finishing procedures.

1. After screening and cleaning floor, allow to dry thoroughly.
2. Using "Blue Painters Tape", tape off lines to be repainted.
3. Using one of the approved paints (listed below), paint the entire line to ensure consistent color (2 thin coats are better than 1 thick coat). Pull tape before paint tacks up. Allow paint to dry 24-48 hours with good ventilation (some solvent-based dark paints may take up to 5 days to completely dry in adverse drying conditions).

APPROVED PAINTS:

Solvent-Based Paints:

- 1 Shot Sign Painters' Lettering Enamel.
- Ace Indoor/ Outdoor Rust Stop
- Sherwin Williams Industrial & Marine Enamel
- Anchor Paints Saf-T-Gard II Enamel
- Devoe Devguard Alkyd Industrial Gloss Enamel
- MAB Rust-O-Lastic High Gloss Alkyd
- Porter Glyptex Urethane Enamel

Water-Based Paints:

- Sherwin Williams Armor Seal Tread Plex
- Sherwin Williams Armor Seal 1K
- Coronado Rust Scat Latex High Gloss
- Ace Royal Interior/ Exterior Hi-Gloss
- PPG Pitt Tech DTM Acrylic
- Glidden Interior/ Exterior Premium Paint.

Buckeye International, Inc.

2700 Wagner Place • Maryland Heights • MO 63043 • USA • 314.291.1900
www.buckeyeinternational.com

5. Buff paint with a 3M SPP Pad (3M Surface Prep Pad) to TOTALLY roughen and dull the paint before coating the gym floor.
6. Tack off paint dust with a cotton bath towel soaked in Screen Clean Ready to Use Floor Prep Cleaner and Tacking Solution. Allow floor to dry at least 30 minutes after tacking.
7. After the floor is dry, make sure your shoes are clean and apply the Buckeye Reflections wood floor coating of choice according to label directions.
8. Note: Gym Bond may be used to provide extra adhesion both under and over the paint. Please see the Gym Bond literature for information on how to apply.

Issued: 8/30/2017

Supersedes: 6/23/2016