



# Safety Data Sheet

Issue Date: 27-Dec-2011

Revision Date: 04-Feb-2015

Version 1

## 1. IDENTIFICATION

### Product Identifier

**Product Name** Buckeye Coliseum 100

### Other means of identification

**SDS #** BE-5186  
**Product Code** 5186  
**UN/ID No** UN1263

### Recommended use of the chemical and restrictions on use

**Recommended Use** Oil Modified Wood Floor Sanding Seal.

### Details of the supplier of the safety data sheet

#### Supplier Address

Buckeye International, Inc.  
2700 Wagner Place  
Maryland Heights, MO 63043 USA

### Emergency Telephone Number

**Company Phone Number** 1-651-632-8956 (International)  
1-800-303-0441 (North America)  
**Emergency Telephone (24 hr)** INFOTRAC 1-352-323-3500 (International)  
1-800-535-5053 (North America)

## 2. HAZARDS IDENTIFICATION

**Appearance** Clear, light amber liquid

**Physical State** Liquid

**Odor** Mineral spirits

### Classification

Acute toxicity - Inhalation (Vapors)	Category 4
Aspiration toxicity	Category 1
Flammable Liquids	Category 3

### Hazards Not Otherwise Classified (HNOC)

May be harmful in contact with skin  
Causes mild skin irritation

### Signal Word

**Danger**

### Hazard Statements

Harmful if inhaled  
May be fatal if swallowed and enters airways  
Flammable liquid and vapor

**Precautionary Statements - Prevention**

Avoid breathing dust/fume/gas/mist/vapors/spray  
 Use only outdoors or in a well-ventilated area  
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use explosion-proof equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge  
 Wear protective gloves/protective clothing/eye protection/face protection

**Precautionary Statements - Response**

IF ON SKIN: Wash with plenty of soap and water  
 Take off contaminated clothing and wash it before reuse  
 Seek medical attention if symptoms develop and persist  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
 Get medical attention if symptoms persist  
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
 Do not induce vomiting  
 IN CASE OF FIRE: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**Precautionary Statements - Storage**

Store locked up  
 Store in a well-ventilated place. Keep cool

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Other Hazards**

Toxic to aquatic life with long lasting effects

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Petroleum Distillates, Hydrotreated light	64742-47-8	>33
Naphtha (petroleum), heavy straight-run	64741-41-9	5.62
Xylene	1330-20-7	4.06
Ethylbenzene	100-41-4	0.85

\*\*If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.\*\*

## 4. FIRST-AID MEASURES

### First Aid Measures

<b>Eye Contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
<b>Skin Contact</b>	Wash skin with soap and water. Take off contaminated clothing and wash it before reuse. Get medical attention if irritation develops or persists.
<b>Inhalation</b>	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, give artificial respiration. Get medical attention if symptoms persist.
<b>Ingestion</b>	Give two large glasses of water; give milk if available. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Immediately call a poison center or doctor/physician.

### Most important symptoms and effects

<b>Symptoms</b>	Moderate eye and skin irritant. Harmful if inhaled, ingested, or absorbed through skin. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. May cause liver damage, kidney damage, and central nervous system depression. May be harmful or fatal if swallowed and enters airways.
-----------------	---

### Indication of any immediate medical attention and special treatment needed

<b>Notes to Physician</b>	Treat symptomatically.
---------------------------	------------------------

## 5. FIRE-FIGHTING MEASURES

### Suitable Extinguishing Media

Carbon dioxide (CO<sub>2</sub>). Dry chemical. Foam. Water spray (fog).

**Unsuitable Extinguishing Media** Not determined.

### Specific Hazards Arising from the Chemical

Flammable liquid and vapor. Combustion products may be toxic.

**Hazardous Combustion Products** Carbon oxides. Halogenated compounds. Nitrogen compounds.

**Sensitivity to Static Discharge** Take precautionary measures against static discharge.

### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use water spray to keep fire-exposed containers cool.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

<b>Personal Precautions</b>	Use personal protection recommended in Section 8.
<b>Environmental Precautions</b>	Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information. See Section 13: DISPOSAL CONSIDERATIONS.

**Methods and material for containment and cleaning up**

<b>Methods for Containment</b>	Prevent further leakage or spillage if safe to do so.
<b>Methods for Clean-Up</b>	Pick up with dry mop, absorbent material, towels, or rags. Clean area with mineral spirits. Allow residue to evaporate. Allow floor to dry before allowing traffic.

**7. HANDLING AND STORAGE****Precautions for safe handling**

<b>Advice on Safe Handling</b>	Handle in accordance with good industrial hygiene and safety practice. Use personal protection recommended in Section 8. Avoid contact with skin, eyes or clothing. Avoid breathing vapors or mists. Use only outdoors or in a well-ventilated area. Wash thoroughly with soap and water after handling. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion proof equipment. Use only non-sparking tools. Take precautionary measures against static discharges. Keep containers closed when not in use. Do not cut, weld, or puncture container.
--------------------------------	---

**Conditions for safe storage, including any incompatibilities**

<b>Storage Conditions</b>	Keep container tightly closed and store in a cool, dry and well-ventilated place. Store at room temperature. Do not store at temperatures above 120°F. Store locked up.
<b>Incompatible Materials</b>	Avoid water reactive materials, heat, or contact with peroxides or other catalysts.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION****Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Xylene 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m <sup>3</sup> (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m <sup>3</sup>	-
Ethylbenzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m <sup>3</sup> (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m <sup>3</sup>	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 125 ppm STEL: 545 mg/m <sup>3</sup>

**Appropriate engineering controls**

<b>Engineering Controls</b>	Ensure adequate ventilation, especially in confined areas. Eyewash stations. Showers.
-----------------------------	---

**Individual protection measures, such as personal protective equipment**

<b>Eye/Face Protection</b>	Risk of contact: Wear approved safety goggles.
<b>Skin and Body Protection</b>	Wear rubber gloves or other impervious gloves. Wear normal work clothing which covers the skin.
<b>Respiratory Protection</b>	None under normal use. If air monitoring levels demonstrate levels above applicable limits, a properly fitted respirator should be worn during application.

**General Hygiene Considerations** Handle in accordance with good industrial hygiene and safety practice.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

<b>Physical State</b>	Liquid	<b>Odor</b>	Mineral spirits
<b>Appearance</b>	Clear, light amber liquid	<b>Odor Threshold</b>	Not determined
<b>Color</b>	Clear, light amber		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	Not applicable	
Melting Point/Freezing Point	Not determined	
Boiling Point/Boiling Range	139 °C / 282 °F	
Flash Point	40.5 °C / 105 °F	
Evaporation Rate	0.9	(butyl acetate = 1)
Flammability (Solid, Gas)	Liquid-Not applicable	
Upper Flammability Limits	10.0%	
Lower Flammability Limit	1.0%	
Vapor Pressure	Not determined	
Vapor Density	Not determined	
Specific Gravity	0.88	
Water Solubility	Insoluble in water	
Solubility in other solvents	Not determined	
Partition Coefficient	Not determined	
Auto-ignition Temperature	Not determined	
Decomposition Temperature	Not determined	
Kinematic Viscosity	Not determined	
Dynamic Viscosity	Not determined	
Explosive Properties	Not determined	
Oxidizing Properties	Not determined	

## 10. STABILITY AND REACTIVITY

### Reactivity

Not reactive under normal conditions.

### Chemical Stability

Stable under recommended storage conditions.

### Possibility of Hazardous Reactions

None under normal processing.

<b>Hazardous Polymerization</b>	Hazardous polymerization does not occur.
---------------------------------	--

### Conditions to Avoid

Keep separated from incompatible substances. Keep out of reach of children.

### Incompatible Materials

Avoid water reactive materials, heat, or contact with peroxides or other catalysts.

### Hazardous Decomposition Products

Carbon oxides. Halogenated compounds. Nitrogen compounds.

## 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

#### Product Information

<b>Eye Contact</b>	Avoid contact with eyes.
<b>Skin Contact</b>	May be harmful in contact with skin. Causes mild skin irritation.
<b>Inhalation</b>	Harmful if inhaled.
<b>Ingestion</b>	May be fatal if swallowed and enters airways.

### Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Petroleum Distillates, Hydrotreated light 64742-47-8	> 5000 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	> 5.2 mg/L ( Rat ) 4 h
Xylene 1330-20-7	= 4300 mg/kg ( Rat )	> 1700 mg/kg ( Rabbit )	= 5000 ppm ( Rat ) 4 h = 47635 mg/L ( Rat ) 4 h
Ethylbenzene 100-41-4	= 3500 mg/kg ( Rat )	= 15354 mg/kg ( Rabbit )	= 17.2 mg/L ( Rat ) 4 h

### Information on physical, chemical and toxicological effects

**Symptoms** Please see section 4 of this SDS for symptoms.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Carcinogenicity** Ethylbenzene has been classified by IARC as 'possibly carcinogenic to humans' based on carcinogenicity in lab animals only.

Chemical Name	ACGIH	IARC	NTP	OSHA
Xylene 1330-20-7		Group 3		
Ethylbenzene 100-41-4	A3	Group 2B		X

#### Legend

**ACGIH (American Conference of Governmental Industrial Hygienists)**

A3 - Animal Carcinogen

**IARC (International Agency for Research on Cancer)**

Group 2B - Possibly Carcinogenic to Humans

Group 3 IARC components are "not classifiable as human carcinogens"

**OSHA (Occupational Safety and Health Administration of the US Department of Labor)**

X - Present

**Aspiration hazard** May be fatal if swallowed and enters airways.

### Numerical measures of toxicity

Not determined

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Toxic to aquatic life with long lasting effects.

**Component Information**

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Petroleum Distillates, Hydrotreated light 64742-47-8		45: 96 h Pimephales promelas mg/L LC50 flow-through 2.2: 96 h Lepomis macrochirus mg/L LC50 static 2.4: 96 h Oncorhynchus mykiss mg/L LC50 static		
Naphtha (petroleum), heavy straight-run 64741-41-9	4700: 72 h Pseudokirchneriella subcapitata mg/L EC50			
Xylene 1330-20-7		13.4: 96 h Pimephales promelas mg/L LC50 flow-through 2.661 - 4.093: 96 h Oncorhynchus mykiss mg/L LC50 static 13.5 - 17.3: 96 h Oncorhynchus mykiss mg/L LC50 13.1 - 16.5: 96 h Lepomis macrochirus mg/L LC50 flow-through 19: 96 h Lepomis macrochirus mg/L LC50 7.711 - 9.591: 96 h Lepomis macrochirus mg/L LC50 static 23.53 - 29.97: 96 h Pimephales promelas mg/L LC50 static 780: 96 h Cyprinus carpio mg/L LC50 semi-static 780: 96 h Cyprinus carpio mg/L LC50 30.26 - 40.75: 96 h Poecilia reticulata mg/L LC50 static	EC50 = 0.0084 mg/L 24 h	3.82: 48 h water flea mg/L EC50 0.6: 48 h Gammarus lacustris mg/L LC50
Ethylbenzene 100-41-4	4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 438: 96 h Pseudokirchneriella subcapitata mg/L EC50 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 1.7 - 7.6: 96 h Pseudokirchneriella subcapitata mg/L EC50 static	11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static 4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 7.55 - 11: 96 h Pimephales promelas mg/L LC50 flow-through 32: 96 h Lepomis macrochirus mg/L LC50 static 9.1 - 15.6: 96 h Pimephales promelas mg/L LC50 static 9.6: 96 h Poecilia reticulata mg/L LC50 static	EC50 = 9.68 mg/L 30 min EC50 = 96 mg/L 24 h	1.8 - 2.4: 48 h Daphnia magna mg/L EC50

**Persistence/Degradability**

Not determined.

**Bioaccumulation**

Not determined.

**Mobility**

Chemical Name	Partition Coefficient
Xylene 1330-20-7	3.15
Ethylbenzene 100-41-4	3.118

**Other Adverse Effects**

Not determined

**13. DISPOSAL CONSIDERATIONS**

**Waste Treatment Methods**

**Disposal of Wastes** Disposal should be in accordance with applicable regional, national and local laws and regulations.

**Contaminated Packaging** Disposal should be in accordance with applicable regional, national and local laws and regulations.

**US EPA Waste Number**

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Xylene 1330-20-7		Included in waste stream: F039		U239
Ethylbenzene 100-41-4		Included in waste stream: F039		

**California Hazardous Waste Status**

Chemical Name	California Hazardous Waste Status
Xylene 1330-20-7	Toxic Ignitable
Ethylbenzene 100-41-4	Toxic Ignitable

**14. TRANSPORT INFORMATION**

**Note** Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

**DOT**

**UN/ID No** UN1263  
**Proper Shipping Name** Paint  
**Hazard Class** 3  
**Packing Group** III

**IATA**

**UN/ID No** UN1263  
**Proper Shipping Name** Paint  
**Hazard Class** 3  
**Packing Group** III

**IMDG**

**UN/ID No** UN1263  
**Proper Shipping Name** Paint  
**Hazard Class** 3  
**Packing Group** III



## 15. REGULATORY INFORMATION

### International Inventories

Chemical Name	TSCA	DSL	NDSL	EINECS	ELINCS	ENCS	IECSC	KECL	PICCS	AICS
Petroleum Distillates, Hydrotreated light	Present	X		Present		Present	X	Present	X	X
Naphtha (petroleum), heavy straight-run	Present	X		Present			X	Present	X	X
Xylene	Present	X		Present		Present	X	Present	X	X
Ethylbenzene	Present	X		Present		Present	X	Present	X	X

#### Legend:

*TSCA - United States Toxic Substances Control Act Section 8(b) Inventory*

*DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List*

*EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances*

*ENCS - Japan Existing and New Chemical Substances*

*IECSC - China Inventory of Existing Chemical Substances*

*KECL - Korean Existing and Evaluated Chemical Substances*

*PICCS - Philippines Inventory of Chemicals and Chemical Substances*

*AICS - Australian Inventory of Chemical Substances*

### US Federal Regulations

#### CERCLA

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Xylene 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
Ethylbenzene 100-41-4	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

#### SARA 313

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Xylene - 1330-20-7	1330-20-7	4.06	1.0
Ethylbenzene - 100-41-4	100-41-4	0.85	0.1

#### CWA (Clean Water Act)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Xylene	100 lb			X
Ethylbenzene	1000 lb	X	X	X

### US State Regulations

#### California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Ethylbenzene - 100-41-4	Carcinogen

#### U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Xylene 1330-20-7	X	X	X
Ethylbenzene 100-41-4	X	X	X

<b>16. OTHER INFORMATION</b>
------------------------------

<b><u>NFPA</u></b>	<b>Health Hazards</b>	<b>Flammability</b>	<b>Instability</b>	<b>Special Hazards</b>
	2	2	1	Not determined
<b><u>HMIS</u></b>	<b>Health Hazards</b>	<b>Flammability</b>	<b>Physical Hazards</b>	<b>Personal Protection</b>
	Not determined	Not determined	Not determined	Not determined

**Issue Date:** 27-Dec-2011  
**Revision Date:** 04-Feb-2015  
**Revision Note:** New format

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**